

# iData 25T 2-in-1 Smart Thermometer



## ➤ Non-contact industrial temperature measurement, multiple temperature measurement modes

- ◆ 0 ~ 6cm non-contact safety temperature measurement, providing more protection
- ◆ Multiple temperature measurement modes
- ◆ Intelligently sense ambient temperature, meeting all temperature measurement requirements in 0 ~ 40 ° C environment
- ◆ Built-in German Hyman thermopile sensor, accurate to  $\pm 0.2^{\circ}\text{C}$ , within  $\leq 1\text{s}$

## ➤ Real-time reading of city code / health code / smart ID card / access card

- ◆ Real-time reading of city code / health code / ID card information: detection + identification + entry information in one step, improving operation efficiency
- ◆ NFC personnel access card, ID card + access card for quick verification and reading, meeting the requirements of a Visitor Management System

## ➤ Wi-Fi data transmission + camera / video recording, with personnel information collection capabilities

- ◆ Wi-Fi data transmission, timely and efficient information transmission and upload
- ◆ 8 MP HD camera, to capture barcode & QR code data, such as on ticketing or cards

### ➤ Local/cloud storage & background system & big data platform

- ◆ Personnel information admission can choose multiple local / cloud storage schemes
- ◆ The backstage can inquire about the visits of people in and out of the enterprise / community / park in real time, and it can be displayed on a map.
- ◆ Big data platform AI intelligent processing, personnel information details are intelligently sorted and updated to ensure real-time + timely control measures are in place

### ➤ Long battery life+ long temperature measurement life

- ◆ Equipped with 2700mAh large capacity battery;
- ◆ Over 1 million times of temperature measurement button life, easily covering over one million people's temperature measurement needs.

### ➤ Enterprise-class configuration

- ◆ Enterprise-class Android OS
- ◆ Enterprise-class Wi-Fi data communication
- ◆ Supporting Bluetooth 4.2 LE communication
- ◆ Slim design, weighing only 170g, making it easier on the user during hours of use
- ◆ Robust and reliable, meeting the drop standard of 1.5 metres high to a concrete floor

## System Configuration

CPU	Quad-core 1.3 GHz
Operating System	Android 8.1 Go
Memory	8GB ROM + 1GB RAM
Display	2.4 inch, 320*240 high resolution
Touch Panel	Capacitive touch panel
Camera	8 MXP autofocus camera in the back side
Keypad	21 front keys, 2 side keys, Power key (total 24 keys)
Battery	3.8 V 2700mAh rechargeable lithium polymer battery
Charging	Supporting Type-C charging
Notification	Vibrator alerts/LED/Audio notification
Vibration Motor	Built-in programmable vibration motor
Sensor	G-Sensor
Intercom function	One-touch PTT call (optional)

## Structural Parameters

Dimensions (LxWxD)	150mm x 54mm x 20mm
Weight	170g (battery included)

## Communication Transmission

Wireless LAN	Wi-Fi 802.11 a/b/g/n (Dual-band Wi-Fi: 2.4G+5G)
Bluetooth	Bluetooth 4.2 LE

## Operating Environment

Programming Language	Android Standard interface, Java, Secondary development SDK , API , DEMO
Operating Temp.	-20°C ~ 60°C (-4°F ~ 140°F)
Storage Temp.	-40°C ~ 60°C ( -40°F ~140°F ) battery included
Relative Humidity	0 ~ 95% (non-condensing)
Drop Specification	1.5-meter drops to concrete ground
Electrostatic Discharge	Conforms to ±15 kV air discharge, ±8 kV direct discharge

## Temperature detection parameters

Measurement method	Non-contact / infrared
Measuring distance	0~6cm
Response Time	≤1S
Temperature Range	Normal mode: 32 ~ 42.9 °C Object mode: 0 ~ 100 °C
Resolution	0.01°C
Measurement accuracy	Normal mode 35 °C ~ 42 °C ± 0.2 °C, other ranges ± 0.3 °C Object mode ± 1.0 °C
Clinical reusability	±0.3°C
Operating environment	Temperature 0 ~ 40 °C, relative humidity ≤85% Rh, air pressure 60-110Kpa

## NFC

Frequency	13.56 MHz
Reading Distance	Within 30 mm
Protocol	ISO14443A/14443B/15693

## Input/output Ports

USB Port	1 (Type-C USB port)
----------	---------------------

## Accessories

Standard	USB Cable, Hand strap
Optional	Power adapter

*iData*<sup>®</sup>

CFI GLOBAL

39 Venture Drive

E-mail: [sales@cfglobal.com](mailto:sales@cfglobal.com)Website: [www.cfglobal.com.au](http://www.cfglobal.com.au)