



™ Wearable SF1




Ideal for order picking and repeat scanning



Sort large amounts of packages quickly



Keep hands free to receive goods and multi-task





WEARABLE SCANNER Wearable SF1



Switch easily from wearing or holding scanner with wireless design

Newly developed switching technology enables the contactless connection between a scanner and an external trigger. The wireless structure avoids the risk of disconnection and breakage. If a scanner is removed from the attachment, it can operate as a mobile scanner.



Wearable attachment with unique material ensures comfortable operation anytime

Attachment base is made of highly moistureabsorbing material that reduces friction on skin and is easily washable for a clean and comfortable

*The scanner holder is not washable. Please read the enclosed operator's guide.



Lightweight magnesium frame provides top-notch drop impact resistance

The durable magnesium frame is perfect for tough workplaces and withstands a height drop test of up to 2.5 m, all while remaining lightweight and comfortable.

Wearable SF1 configuration

A + B + C

Туре			2D code model
			SF1-QBi-T
Case color			Dark gray
Scanning mode	Mode		Area sensor
	Readable codes	2D codes	QR Code, SQRC, Micro QR Code, DataMatrix (ECC200), PDF417, Micro PDF417, Maxicode, Aztec, GS1 Composite
		1D codes	EAN-13/8, UPC-A/E, UPC/EAN (with add-on), Interleaved 2 of 5, Standard 2 of 5, Codabar (NW-7), CODE39, CODE93, CODE128, GS1-128 (EAN-128), GS1 DataBar (RSS
	Minimum resolution	2D codes	0.167 mm
		1D codes	0.125 mm
	PCS value		0.3 min
	Angle		+/ - 50°
	Scanning confirmation		Confirmation LEDs (blue, green, red), Beeper, Vibrator
Communication interface	Method		Bluetooth Ver.2.1 + EDR-based class 2
	Profile		SPP, H I D, SPP (for iOS)
Power	Source		Lithium ion battery
	Operating time*1		24 hours
	Charging time		2.5 hours
Environment requirements	Degree of protection		IP54
	Drop impact resistance*2		2.5 m, 1.5 m x 100 times, Tumbling test: 0.5 m x 3,000 times
	Operating temperature*3		-20 ℃ to 50 ℃
	Operating humidity		10 to 90%RH (No dew condensation and freezing)
	Operating illuminance		10,000 lux max. (Under daylight fluorescent light)
Weight			Approx. 80 g
Trigger switch			Button type or touch type
iOS supporting models			Made for iPhone X, iPhone 8, iPhone 8 Plus, iPad Pro 12.9-inch (2nd generation), iPad Pro 10.5-inch, iPad (5th generation), and iPod touch (6th generation)

Wearable scanner Wearable SF1	
B+C-	_
	A Scanner SF1-QBi-T
Wearable attachment AW2-001-R	
	B Scanner holder AW4-001-R
	Base AW3-001-R Washable

^{*1} When one reading pass over a 5-second period. *2 These are test values, but not guaranteed values. *3 It becomes 0° to 40° C when charging.

Wearable attachment

Model	AW2-001-R
Color	Black and cyan blue
Trigger switch	Button type
Weight	Approx. 50 g

Contents

- Scanner: SF1-QBi-T
- Operator's guide
- Wearable attachment (sold separately): AW2-001-R
- User's manual 🖳

Software

- Keyboard interface software (QR_kbif) Ψ
- Scanner Setting 2D 🖳
- SQRC®Setting
- BA Setting 🖳
- DENSO SF1 SDK for iOS 🖳

Items with this mark can be downloaded from our website (QBdirect) free of charge.

Option (sold separately)

- Charger
 - Main unit charger: CH-SF11 Quadruple charger: CH-SF14
- Bluetooth communication unit BA20-RU BA11-RKU

'Made for iPhone', 'Made for iPad', and 'Made for iPod' means that an accessory has been designed to connect specifically to the iPhone, iPad, or iPod, and has been certified by the developer to meet Apple performance standards.

Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards.

Apple, iPad, iPad Pro, iPod, iPod touch, and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. The trademark "iPhone" is

Apple, IPAD, IPAD IPAD, IPAD TO, IPAD T

Data as of December 2018 are described on this catalogue.

Before using this product, please read it's user's manual thoroughly for correct use.